



TDS: 035  
Rev. 2.0

Ciber s.r.l.  
Via Lazzaro Spallanzani, n.8  
24061 - Albano Sant'Alessandro  
Bergamo - Italy  
Tel: (+39) 035.581.427  
E-mail: info@cibersrl.it

STONE PROTECTION – WATER BASED

# ACCADUEO

**Description:** ANTI STAIN WATER BASED IMPREGNATOR TREATMENT MARBLE TERRAZZO.

**ECO-FRIENDLY PRODUCT & NO SOLVENT INSIDE**

**Recommended Use:** POLISHED AND HONED MATT TEXTURED FINISH MARBLE TERRAZZO, GRANITE, MARBLE, NATURAL AND ARTIFICIAL ENGINEERED STONES, TERRA COTTA, QUARRY, CEMENT PAVERS.

- Natural finish for interior and exterior use.
- Effective for honed and polished natural stones - Flooring –Work surfaces (Kitchen, Bathrooms)
- Effective as pre- grouting treatment

**Properties:** ACCADUEO penetrates the surface of the stone creating an invisible barrier protection against stains: - Oil, Grease, Coffee, Tea, Food, General Dirt, Mould and Mildew. Product will **not change** the natural aspect of the stone or create any type of film, allowing permeability vapour moisture to escape, and is UV- resistant. Some natural stones (marble, limestone) will remain sensitive to acidic etching, we recommend any spillage be cleaned up as a matter of good housekeeping.

**Important Safety Note:** When using any type of product suitable ventilation should be provided during and after application .Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product. Keep product well closed and out of the reach from children.

Additional information available on Material Safety Data Sheet.

**STORAGE:** - Keep product in cool and dry surroundings.

**Application:** All stone surfaces to be treated must be completely clean and dry.

Where no previous treatment experience exists a small discreet area should be tested to verify the suitability of the product to the stone.

Apply one coat of ACCADUEO evenly by spraying using a low pressure pump up garden spray type unit or with a lamb's wool applicator or by cloth in circular movements. The most efficient method is by spraying. On very absorbent surfaces apply a second or third coat allowing sufficient time between each application (20-30 minutes) to penetrate into the stone and dry.

If in doubt test discreet area to ensure second or third application is necessary.

In case of over treatment or any air bubbles remove by wiping excess product using a clean cotton cloth or absorbent paper.

Temperature of surface to be treated should not be below 10°C. Avoid direct sunlight especially for external works.

**Drying time:** - Dry 2 to 3 hours, safe to walk on carefully .Fully effective within 48-72 hours before resuming normal use.

**Pre Grout Treatment:** - Product can be applied while stone is damp.

Apply over clean stone or tile surface minimum 3 hours before grouting.

Final stone protection can be carried out with water based treatment later once stone clean and dry.

**ALWAYS TEST FIRST**

## COVERAGE PER LT:

Indicative coverage allowing 2 coats subject to stone absorption, surface texture.

- High Porosity Stone, Sandstone 3 – 5m<sup>2</sup>
- Medium Porosity, Honed Stone, Limestone 6 – 10m<sup>2</sup>
- Low Porosity, Polished Stone 10 – 20m<sup>2</sup>
- Very Dense Stone 25 – 30m<sup>2</sup>

## Packaging:

10 x 1 litre Bottles

2 x 5 litre container

25 litre container

All childproof tamper evident cap

## MAINTENANCE:

Flooring and work tops routine cleaning antibacterial

**CIBERNET.** Intensive or periodic clean where

additional effort is required we recommend using **CIBERPLUS** detergent. Certain stone surfaces have open microscopic pores where ingrained dirt settles, here you can apply our product **MIX PLUS** which will create an easy care surface solution. (See technical data sheet for further information)