# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



# TEC7 CLEANER AEROSOL

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

: TEC7 CLEANER AEROSOL Product name Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

#### 1.2.2 Uses advised against

No uses advised against known

### 1.3. Details of the supplier of the safety data sheet

### Supplier of the safety data sheet

TEC7\*

Industrielaan 5B

B-2250 Olen

**2** +32 14 85 97 37

**4** +32 14 85 97 38

info@tec7.be

\*TEC7 is a registered trademark of Novatech International N.V.

#### Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

**2** +32 14 85 97 37

**4** +32 14 85 97 38

info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (FC) No. 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements





Contains: hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics.

Signal Word	Dangei
H-statements	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

P-statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P211 Do not spray on an open flame or other ignition source.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be

© BIG vzw

Reason for revision: 3, 8, 15 Revision number: 0501

Publication date: 2010-07-09 Date of revision: 2022-01-30

BIG number: 49027

P251 Do not pierce or burn, even after use.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

# SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119471843-32	927-241-2	C≤80%	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 3; H412 EUH066	(1)(10)	UVCB	
propane 01-2119486944-21	74-98-6 200-827-9	C≤20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
butane 01-2119474691-32	106-97-8 203-448-7	C≤9%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	

<sup>(1)</sup> For H- and EUH-statements in full: see section 16

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

# SECTION 4: First aid measures

### 4.1. Description of first aid measures

### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.2.1 Acute symptoms

# After inhalation:

Dizziness. Drowsiness.

### After skin contact:

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

#### After eye contact: No effects known.

# After ingestion:

After ingestion: No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

Reason for revision: 3, 8, 15 Publication date: 2010-07-09

Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 2 / 12

<sup>(2)</sup> Substance with a Community workplace exposure limit

<sup>(10)</sup> Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

<sup>(21) 1.3-</sup>butadiene < 0.1%

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

#### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

#### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

#### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

#### 6.4. Reference to other sections

See section 13.

# SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

### 7.2. Conditions for safe storage, including any incompatibilities

# 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight. Protect against frost.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

# 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

# SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

### 8.1.1 Occupational exposure

# a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

Reason for revision: 3, 8, 15

Publication date: 2010-07-09

Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027

3 / 12

Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

#### France

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non	800 ppm
	réglementaire indicative)	
	Time-weighted average exposure limit 8 h (VL: Valeur non	1900 mg/m³
	réglementaire indicative)	

#### Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m³

#### Austria

Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Tagesmittelwert (MAK)	800 ppm
	Tagesmittelwert (MAK)	1900 mg/m³
	Kurzzeitwert 60(Mow) 3x (MAK)	1600 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m <sup>3</sup>
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m³
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m <sup>3</sup>

#### UK

Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	1450 mg/m³
	750 ppm
Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m³

#### **USA (TLV-ACGIH)**

	In the second of	
Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm

### b) National biological limit values

If limit values are applicable and available these will be listed below.

#### 8.1.2 Sampling methods

If applicable and available it will be listed below.

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

### 8.1.4 Threshold values

### **DNEL/DMEL - Workers**

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	871 mg/m³	
	Long-term systemic effects dermal	77 mg/kg bw/day	

DNEL/DMEL - General population hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

, ar e car s e ris) es e 2 e) ir amaries)	yar bar sens, es eze, il amaries, isoamaries, et en are		
Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	185 mg/m³	
	Long-term systemic effects dermal	46 mg/kg bw/day	
	Long-term systemic effects oral	46 mg/kg bw/day	

# 8.1.5 Control banding

If applicable and available it will be listed below.

#### 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Reason for revision: 3, 8, 15 Publication date: 2010-07-09

Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 4/12

Full face mask with filter type A at conc. in air > exposure limit.

Protective gloves against chemicals (EN 374).

	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

#### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	No data available on colour
Particle size	Not applicable (mixture)
Explosion limits	0.6 - 9.5 vol % ; Propellant
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 °C ; Liquid
Kinematic viscosity	1 mm²/s ; 40 °C ; Liquid
Melting point	Not applicable (aerosol)
Boiling point	-42 °C - 166 °C ; Liquid
Relative vapour density	>1
Vapour pressure	8530 hPa ; 20 °C
Solubility	Water ; insoluble
Relative density	0.76 ; 20 °C ; Liquid
Absolute density	64 kg/m³ ; 20 °C
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
рН	Not applicable (aerosol)

#### 9.2. Other information

Evaporation rate	0.35; Butyl acetate; Liquid	
------------------	-----------------------------	--

# SECTION 10: Stability and reactivity

# 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

#### 10.2. Chemical stability

Unstable on exposure to heat.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

#### **Precautionary measures**

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

# SECTION 11: Toxicological information

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

# 11.1.1 Test results

#### Acute toxicity

#### **TEC7 CLEANER AEROSOL**

No (test)data on the mixture available

Reason for revision: 3, 8, 15 Publication date: 2010-07-09 Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 5/12

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD	> 5000 mg/kg bw			Read-across	
		401			female)		
Dermal	LD50	Equivalent to OECD	> 3160 mg/kg bw	24 h	Rabbit (male /	Experimental value	
		402			female)		
Inhalation (aerosol)	LC50	Equivalent to OECD	> 5.6 mg/l air	4 h	Rat (male /	Experimental value	
		403			female)		

#### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

#### TEC7 CLEANER AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye		Equivalent to OECD 405		1; 24; 48; 72; 168 hours			Single treatment
Skin		Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

#### Conclusion

Not classified as irritating to the respiratory system

Not classified as irritating to the skin

Not classified as irritating to the eyes

#### Respiratory or skin sensitisation

#### **TEC7 CLEANER AEROSOL**

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD	24; 48 hours	1 1 0	Read-across	
		406		(female)		

#### Conclusion

Not classified as sensitizing for skin

# Specific target organ toxicity

# TEC7 CLEANER AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 422	> 1000 mg/kg bw/day		No effect		Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	> 10400 mg/m³ air			13 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation			STOT SE cat.3		Drowsiness, dizziness			Literature study

# Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

#### Mutagenicity (in vitro)

# TEC7 CLEANER AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	
activation, negative					
without metabolic					
activation					

Reason for revision: 3, 8, 15 Publication date: 2010-07-09

Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 6 / 12

# Mutagenicity (in vivo)

### TEC7 CLEANER AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD	5 days (6h / day)	Rat (male / female)		Read-across
	478				

#### Conclusion

Not classified for mutagenic or genotoxic toxicity

#### Carcinogenicity

### TEC7 CLEANER AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
exposure								
Inhalation	NOAEC	Equivalent to	≥ 2200	105 weeks (6h / day,	Rat (female)	No carcinogenic		Read-across
(vapours)		OECD 453	mg/m³ air	5 days / week)		effect		

### Conclusion

Not classified for carcinogenicity

### Reproductive toxicity

#### TEC7 CLEANER AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	- 0-	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	≥ 5220 mg/m³ air	10 days (6h / day)	Rat	No effect		Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	> 5220 mg/m³ air	10 days (6h / day)	Rat	No effect		Read-across
Effects on fertility	NOAEL	Equivalent to OECD 413	> 1000 mg/kg bw/day	14 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Read-across

#### Conclusion

Not classified for reprotoxic or developmental toxicity

### Toxicity other effects

# TEC7 CLEANER AEROSOL

Classification is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
exposure								determination
Skin					Skin dryness or			Literature study
					cracking			

#### Conclusion

Repeated exposure may cause skin dryness or cracking.

# Chronic effects from short and long-term exposure

# TEC7 CLEANER AEROSOL

No effects known.

### 11.2. Information on other hazards

No evidence of endocrine disrupting properties

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

# TEC7 CLEANER AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

Reason for revision: 3, 8, 15 Publication date: 2010-07-09

Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 7 / 12

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

yarocarbons, es ero, ir alkaries,	isoumanies, eye	100, 1270 01011						
	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	10 mg/l - 30 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	22 mg/l - 46 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	NOEL	OECD 201	< 1 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEL		0.182 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOELR		0.317 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Nominal concentration

#### Conclusion

Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

**Biodegradation water** 

Method	Value	Duration	Value determination
OECD 301F	89 %	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	18.679 h	1.5E6 /cm <sup>3</sup>	Calculated value

#### Conclusion

#### Water

Does not contain any not readily biodegradable component(s)

#### 12.3. Bioaccumulative potential

#### **TEC7 CLEANER AEROSOL**

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### **BCF** fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	551.7 l/kg; Fresh			Estimated value
		weight			

# Log Kow

_	-6 ····				
	Method	Remark	Value	Temperature	Value determination
			4.66		Evnerimental value

#### Conclusion

Contains bioaccumulative component(s)

# 12.4. Mobility in soil

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	2.380	Calculated value

#### Percent distribution

Method	Fraction air	Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model	34.9 %	0.553 %	1.19 %	63.4 %	Calculated value
Level III					

#### Conclusion

Contains component(s) with potential for mobility in the soil

### 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

# 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

### 12.7. Other adverse effects

### TEC7 CLEANER AEROSOL

#### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Reason for revision: 3, 8, 15

Publication date: 2010-07-09

Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 8 / 12

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

# **SECTION 13: Disposal considerations**

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

#### **European Union**

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 29\* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Specific treatment. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

### 13.1.3 Packaging/Container

#### **European Union**

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

# SECTION 14: Transport information

Road	(ADR)
------	-------

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Rail (RID)

1950
aerosols
23
2
5F
2.1
no
190
327
344
625
Combination packagings: not more than 1 liter per inner packaging for
liquids. A package shall not weigh more than 30 kg. (gross mass)

### Inland waterways (ADN)

Reason for revision: 3, 8, 15 Publication date: 2010-07-09

Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 9 / 12

.1. UN number	
UN number	1950
.2. UN proper shipping name	
Proper shipping name	aerosols
	uc103013
.3. Transport hazard class(es)	
Class	2
Classification code	5F
.4. Packing group	
Packing group	
Labels	2.1
. <u>5. Environmental hazards</u>	
Environmentally hazardous substance mark	no
.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging
Limited quantities	liquids. A package shall not weigh more than 30 kg. (gross mass)
IMDG/IMSBC)	
.1. UN number	
UN number	1950
	1230
.2. UN proper shipping name	paracals
Proper shipping name	aerosols
.3. Transport hazard class(es)	
Class	2.1
.4. Packing group	
Packing group	
Labels	2.1
.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
.6. Special precautions for user	-
Special provisions	190
Special provisions	277
Special provisions	327
	344
Special provisions	381
Special provisions	
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging liquids. A package shall not weigh more than 30 kg. (gross mass)
7. Maritime transport in bulk according to IMO instruments	hi e di
Annex II of MARPOL 73/78	Not applicable
CAO-TI/IATA-DGR)	
.1. UN number UN number	1950
.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
	23.0000) (10.11110000
.3. Transport hazard class(es)	2.1
Class	
.4. Packing group	
Packing group	
Labels	2.1
.5. Environmental hazards	
Environmentally hazardous substance mark	no
.6. Special precautions for user	
	A145
Special provisions	
Special provisions Special provisions	A167
Special provisions	
•	A167 A802

Reason for revision: 3, 8, 15

Publication date: 2010-07-09

Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 10 / 12

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
100.000 %	
709.999 g/l	

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

,	Low tier (tonnes)	Top tier (tonnes)	·	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

Ingredients according to Regulation (EC) No 648/2004 and amendments

≥30% aliphatic hydrocarbons

**REACH Annex XVII - Restriction** 

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances. mixtures and articles.

and use of certain dangerous	substances, mixtures and articles.	Ta mi e i i i
	Designation of the substance, of the group of	Conditions of restriction
	substances or of the mixture	
· hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in:  — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,  — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects,  2. Articles not complying with paragraph 1 shall not be placed on the market.  3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:  — can be used as fuel in decorative oil lamps for supply to the general public, and,  — present an aspiration hazard and are labelled with H304,  4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).  5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:  a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";  b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";  c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:  — metallic glitter intended mainly for decoration,  — artificial snow and frost,  — "whoopee" cushions,  — silly string aerosols,  — imitation excrement,  — horns for parties,  — decorative flakes and foams,  — artificial cobwebs,  — stink bombs.  2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:  "For professional users only".  3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.  4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

National legislation Belgium TEC7 CLEANER AEROSOL

No data available

National legislation The Netherlands

Reason for revision: 3, 8, 15

Publication date: 2010-07-09

Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 11 / 12

#### **TEC7 CLEANER AEROSOL**

Waterbezwaarlijkheid Z (2); Algemene Beoordelingsmethodiek (ABM)

#### **National legislation France**

TEC7 CLEANER AEROSOL

No data available

#### **National legislation Germany**

#### TEC7 CLEANER AEROSOL

	Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge		
	WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017		
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	TA-Luft	5.2.5/I		

#### **National legislation Austria**

TEC7 CLEANER AEROSOL

No data available

#### **National legislation United Kingdom**

**TEC7 CLEANER AEROSOL** 

No data available

#### Other relevant data

TEC7 CLEANER AEROSOL

No data available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

### SECTION 16: Other information

# Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H226 Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

(\*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level

ATE Acute Toxicity Estimate

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3, 8, 15 Publication date: 2010-07-09
Date of revision: 2022-01-30

Revision number: 0501 BIG number: 49027 12 / 12